

SHERPASCOPIC TÉLESCOPIQUE

OPTIMAL COMFORT ON EVERY TYPE OF GROUND

This Tubesca aluminium mobile platform sets the standard for telescopic platforms. Available in several models at heights of up to 4.5 metres with 3-4/4-6/7-9/7-10 steps. Its reinforced uprights, wide platform, adjustable stabilisers and semi-automatic rigid guardrails make the Sherpascopic an extremely robust, stable product. It has a tool carrier, transport wheels and 80 mm steps. It meets the PIR-PIRL standards for mobile platforms, complies with decree 2004-924, standard EN 131-7 and has the NF quality label.



3/4-step model

- ▶ Intuitive high-resistance level offset system.
- ▶ Solid guardrail.
- ▶ Stabilizers with a patented millimetric adjustment system.
- ▶ Non-slip 600 x 420 mm platform with integrated toeboards.
- ▶ Ribbed non-slip rungs crimped in place (30 x 30 mm).
- ▶ Extremely strong handrails.
- ▶ Automatic interlock between the different elements.

Product characteristics

Use	Highly intensive
Type of floor	Flat and uneven floor
Max access / working height (m)	4,46
Material	Aluminium
Maximum load (kg)	150
Warranty (years)	5
Standard	PIR NFP 93353 ; PIR NFP 93352 ; EN 131//7
Decree	2004/924



High reliability gate lock



Ø 160 mm wheels



Rear anti-lift locks



Lifting rings



Evolution of guardrail locking system



SHERPASCOPIC TÉLESCOPIQUE product NF certified
 Certification organization:
 AFNOR Certification - 11, rue Francis de Pressensé, F-93571 LA PLAINE SAINT DENIS CEDEX
 Certification reference system: NF building/works equipment (NF096) available at www.marque-nf.com
 NF mark certifies compliance with standard NF P 93-352 (for Platforms), NF P 93-353 (for light platforms) and with

Delivered in shrink film with POS brochure. The platform is counted as a step. Model 02272250 is certified to be NF PIRL 93353 compliant. Models 02272251 / 02272252 and 02272253 are NF PIR 93352 certified.

Ref.	Folded H (m)	Platform H	Wheelbase (m)	Nb of rungs/steps	Weight (kg)	Access / work H (m)	EAN barcode
02272250	2,13	0,78-1,02	1,39 - 1,57	3-4	23,1	2,78 à 3,02	3178740098698
02272251	2,44	1,07-1,53	1,61 - 1,97	5-7	26,4	3,07 à 3,53	3178740098704
02272252	3,2	1,76-2,23	2,15 - 2,52	8-10	31	3,76 à 4,23	3178740098711
02272253	3,2	1,76-2,46	2,15 - 2,73	8-11	33	3,76 à 4,46	3178740152567