

VELOCE

THE ULTRA-MOBILE PLATFORM

The lightest work platform on the market in an ultra-mobile version. With its retractable wheels, it allows effortless movement even when deployed, to move from one work area to another without being carried. Secure, the 4 wheels retract as soon as the first step is reached. Available from 2 to 7 steps. The range complies with European standard EN 131-7, decree 2004-924 and PIRL standard 93 353 (excluding 7 steps)



- ▶ Available from 2 to 7 steps
- ▶ Retractable wheels Ø75 mm for moving the unit easily when deployed
- ▶ 3-sided rigid guardrail with rear safety straps, and semi-automatic set-up
- ▶ Easy handling
- ▶ Stabilisers to be deployed from 5 steps upwards.
- ▶ The rear stand is designed to pass over obstacles such as toilets (3 and 4 step models)
- ▶ 80 mm non-slip ribbed steps
- ▶ Non-slip platform 500 x 400 mm with integrated toeboards (height: 100 mm)
- ▶ Compartmentalised tool holder. Max load 10kg.

Product characteristics

Use	Regular
Type of floor	Flat floor
Max access / working height (m)	3,64
Material	Aluminium
Maximum load (kg)	150
Warranty (years)	5
Standard	PIRL NFP 93353 ; EN 131-7
Decree	2004/924



Retractable wheels Ø75 mm. No effort required, easy deployment



Stand for passing over toilets, ducting, rails, etc. on 3 and 4 step models



Wide rigid, compartmentalised and ergonomic tool holder as standard.



Non-slip platform with toeboard



Independent folding stabilisers from the 5-step model upwards.



Non-slip steps 80 mm

The platform is counted as a step.

Ref.	Folded H (m)	Platform H	Wheelbase (m)	Nb of rungs/steps	Weight (kg)	Access / work H (m)	EAN barcode
02274012	1,85	0,52	0,95	2	17	2,52	3178740234133
02274013	2,05	0,71	1,1	3	19	2,71	3178740234140
02274014	2,3	0,95	1,25	4	21	2,95	3178740234157
02274015	2,55	1,18	1,4	5	21	3,18	3178740234164
02274016	2,78	1,4	1,55	6	24,5	3,4	3178740234171
02274017	3,05	1,64	1,75	7	28	3,64	3178740234188